Manual Three-piece Ball Valve With Purge Port For Purging Reaction Vessels

Basic Information

Place of Origin: ChinaBrand Name: FABIA

Certification: ISO9001,CE,CCS,DNV
Model Number: 1/8 inch 36 inch

Minimum Order Quantity: 1 setPrice: Negotiable

Packaging Details: Cartons/Wooden casesDelivery Time: 15-30 work days

• Payment Terms: L/C,D/A,D/P,T/T,MoneyGram,Western Union

• Supply Ability: 100-1000 set per week



Product Specification

Product Name: Stainless Steel Three-Piece Ball Valve

Valve Type: FB Ball ValveMaterial: Stainless Steel

Handle: Lever · Package: Carton PTFE Seal Type: 1/2-4 Inch Size: -20~200 Temperature: • Pressure: 150-600 PSI Media: Water, Oil, Gas ANSI, DIN, JIS, GB Standard:

Connection: Threaded, Socket Weld, Butt Weld
Application: Petroleum, Chemical, Power, Etc



More Images







Product Description

Manual Three-piece Ball Valve With Purge Port For Purging Reaction Vessels

1. Description:

The 3-Piece Ball Valve with Purge Port consists of a valve body, a ball body, a valve seat, a valve stem, a seal, and a purge port. It adopts a 3-Piece structure (left valve body, right valve body, and middle valve body) for easy disassembly and maintenance.

Three piece ball valves with blowing ports are suitable for industrial scenarios that require cleaning, blowing, or high sealing requirements, especially in fields such as chemical, food, and pharmaceutical industries where advantages are evident.

2. Specification:

| FABIA Valve Parameter List | |
|----------------------------|---------------------------------------------------------------------------------------------------|
| Valve type: | Ball Valve, Stainless Steel Ball Valve, Three-Piece Ball Valve |
| Size: | 1/2 inch 4 inch |
| Material: | WCB,Q235B,2507,A105,CF8(304),CF8M(316),CF3M (316L),CF3(304L),PVC,ZG1Cr18Ni9Ti,ZG1Cr18Ni12Mo2Ti |
| Connection type: | Welded connection/flange connection/thread connection/clamp connection |
| Driving model: | Manual/Worm gear drive/Pneumatic/Electric |
| Pressure rating: | PN1.0 PN64,ANSI CLASS 150-900,JIS10-20K |
| Temperature: | -20 200 |
| Model: | FB-Q |

3. Features:

Purging function An additional Purge Port is added, which can be used for cleaning, emptying, or inert gas blowing. It is suitable for working conditions with easily residual, easily crystallized, or high-purity media.

Three piece design The valve body can be disassembled for easy internal cleaning, maintenance, or replacement of seals, suitable for industries with high hygiene requirements such as food and medicine.

Good sealing performance PTFE (polytetrafluoroethylene) or other high-performance sealing materials are used, which are corrosion-resistant, heat-resistant, and ensure zero leakage.

Flexible operation Optional handle, gear or pneumatic/electric actuator, suitable for manual or automated control.

Applicable media water, steam, gas, oil, corrosive liquids, high-purity chemicals, etc.





Fabia Valve Industry (Suzhou) Co., Ltd.