



Two Piece Ball Valve Stainless Steel Ball Valve FABIA Industry valves

Our Product Introduction

for more products please visit us on fbballvalve.com

Basic Information

- Place of Origin: China
- Brand Name: FABIA
- Certification: ISO9001,CE,CCS,DNV
- Model Number: 1/8 inch 36 inch
- Minimum Order Quantity: 1 set
- Price: Negotiable
- Packaging Details: Cartons/Wooden cases
- Delivery Time: 15-30 work days
- Payment Terms: L/C,D/A,D/P,T/T,MoneyGram,Western Union
- Supply Ability: 100-1000 set per week



Product Specification

- Product Name: Stainless Steel Three-Piece Ball Valve
- Valve Type: Ball Valve
- Material: Stainless Steel
- Handle: Lever
- Package: Carton
- Seal Type: PTFE
- Size: 1/8-36 Inch
- Temperature: -20~150
- Pressure: 150-600 PSI
- Media: Water, Oil, Gas
- Standard: ANSI, DIN, JIS, GB
- Connection: Threaded, Socket Weld, Butt Weld
- Application: Petroleum, Chemical, Power, Etc



More Images



Product Description

Ball Valve, Stainless Steel Ball Valve, Three-Piece Ball Valve

1. Description:

Three-piece ball valve is a widely used gas valve, with its own advantages, friction-free switch, seal will not be worn, opening and closing torque is small, the optional actuator is mainly compact type to achieve cutting off or adjusting the medium.

Now it is the first choice for gas equipment, petrochemical, aerospace, vacuum equipment, electroplating equipment, agricultural machinery, food machinery, iron and steel metallurgy, HVAC, drying equipment, biopharmaceutical, medical equipment, and other industries.

2. Specification:

FABIA Valve Parameter List	
Valve type:	Ball Valve, Stainless Steel Ball Valve, Three-Piece Ball Valve
Size:	1/8 inch 36 inch
Material:	WCB,Q235B,2507,A105,CF8(304),CF8M(316),CF3M(316L),CF3(304L),PVC,ZG1Cr18Ni9Ti,ZG1Cr18Ni12Mo2Ti
Connection type:	Welded connection/flange connection/thread connection/clamp connection
Driving model:	Manual/Worm gear drive/Pneumatic/Electric
Pressure rating:	PN1.0 PN64,ANSI CLASS 150-900,JIS10-20K
Temperature:	-196 540
Model:	FB-Q...

3. Features:

Fluid resistance is small, ball valve is one of the small fluid resistance of all valves, even the reduced diameter ball valve, its fluid resistance is quite small.

Thrust bearing reduces the friction torque of the valve stem, which can make the valve stem operate smoothly and flexibly for a long time.

Sealing performance of the seat is good, the sealing ring made of polytetrafluoroethylene and other elastic materials, the structure is easy to seal, and the sealing capacity of the ball valve increases with the increase of the medium pressure.

Valve stem seal is reliable, because the valve stem is only as if rotating without lifting movement, the packing seal of the valve stem is not easy to destroy, and the sealing capacity increases with the pressure of the medium.

Because polytetrafluoroethylene and other materials have good self-lubrication, and the friction loss with the ball is small, so the service life of the ball valve is long.

Lower mounted valve stem and valve stem head convex step to prevent the valve stem ejecta, such as fire caused by the valve stem seal damage, the convex step and the valve body can also form metal contact to ensure the valve stem seal.

Anti-static function: set a spring between the ball, valve stem and valve body, which can export the static electricity generated during the switching process .





Fabia Valve Industry (Suzhou) Co., Ltd.



+8618913247051/+8618912658215/+8618260178084



sales@fabia-china.com



fbballvalve.com

Room 1305, Building 3, Jundi Business Plaza, No.3, Weihua Road, Suzhou Industrial Park