



High-quality valve products Pneumatic Fluorine Lined Clamp Butterfly Valve Clamp End

Our Product Introduction

for more products please visit us on fbballvalve.com

Basic Information

- Place of Origin: China
- Brand Name: FABIA
- Certification: ISO9001,CE,CCS,DNV
- Model Number: 1/8 inch 36 inch
- Minimum Order Quantity: 1 set
- Price: Negotiable
- Packaging Details: Cartons/Wooden cases
- Delivery Time: 15-30 work days
- Payment Terms: L/C,D/A,D/P,T/T,MoneyGram,Western Union
- Supply Ability: 100-1000 set per week



Product Specification

- Product Name: Pneumatic Clamp Butterfly Valve
- Valve Type: Pneumatic Butterfly Valve
- Material: Carbon Steel
- Operation: Pneumatic
- Connection: Clamp
- Application: Petroleum, Chemical, Power, Etc.
- Actuator: Pneumatic
- Pressure: 150LB-2500LB
- Sealing: Soft Sealing
- Size: 1/2"-48"
- Temperature: -20 -120



More Images



Product Description

FABIA Pneumatic Fluorine Lined Clamp Butterfly Valve

1. Description:

Pneumatic fluorine lined butterfly valve has a wide temperature range, which is especially suitable for the corrosive medium environment such as strong acid and alkali, and is widely used in chemical agents, factories, dye plants, hydropower stations and other industries.

2. Specification:

FABIA Valve Parameter List	
Valve type:	Pneumatic Fluorine Lined Clamp Butterfly Valve
Size:	2 inch 36 inch
Material:	WCB,GGG40,FCD,SS304,SS304L,SS316,SS316L,ST37(Q235B),SS410
Connection type:	Butt Clamp/Flange Connection
Driving model:	Manual/Worm gear drive/Pneumatic/Electric
Pressure rating:	PN0.1 PN16
Temperature:	-40 1000
Model:	FB-D.....

3. Features:

Pneumatic fluorine lined butterfly valve has scientific design, compact connection between components, small size and small space area.

Pneumatic driving device opens and closes quickly, sensitive induction, labor-saving and convenient for fluid control.

Installation is not limited, it is very suitable for the pipeline with limited installation space, and the later maintenance is very convenient.

Butterfly Valve adopts double sealing structure, and the fluid is not restricted by the space direction when running.

Valve body is made of strong anti-erosion material, and the service time is longer.





Fabia Valve Industry (Suzhou) Co., Ltd.

+8618913247051/+8618912658215/+8618260178084

sales@fabia-china.com

fbballvalve.com

Room 1305, Building 3, Jundi Business Plaza, No.3, Weihua Road, Suzhou Industrial Park