



Pneumatic Soft Seal Butterfly Valve Clamp PVC Valve Lightweight and Cost-Effective

Our Product Introduction

for more products please visit us on fbballvalve.com

Basic Information

- Place of Origin: China
- Brand Name: FABIA
- Certification: ISO9001,CE,CCS,DNV
- Model Number: 1/8 inch 36 inch
- Minimum Order Quantity: 1 set
- Price: Negotiable
- Packaging Details: Cartons/Wooden cases
- Delivery Time: 15-30 work days
- Payment Terms: L/C,D/A,D/P,T/T,MoneyGram,Western Union
- Supply Ability: 100-1000 set per week



Product Specification

- Product Name: Pneumatic Clamp Butterfly Valve
- Valve Type: Pneumatic Butterfly
- Valve Material: PVC
- Valve Actuator: Pneumatic
- Valve Connection: Clamp
- Valve Seal: EPDM
- Valve Disc: PVC
- Valve Pressure: PN16
- Valve Temperature: -30 ~+135



More Images



Product Description

FABIA Soft Seal Pneumatic Clamp Butterfly Valve

1. Description:

Used in petroleum, chemical, light industry, pharmaceutical, paper, automobile and other industrial automatic control system for remote centralized control or local control equipment.

Can be widely used in petroleum, chemical, light industry, pharmaceutical, paper, automobile and other industrial automatic control system for remote centralized control or local control.

2. Specification:

FABIA Valve Parameter List	
Valve type:	Soft Seal Pneumatic Clamp Butterfly Valve
Size:	2 inch 36 inch
Material:	WCB,GGG40,FCD,SS304,SS304L,SS316,SS316L,ST37(Q235B),SS410
Connection type:	Butt Clamp/Flange Connection
Driving model:	Manual/Worm gear drive/Pneumatic/Electric
Pressure rating:	PN0.1 PN16
Temperature:	-40 1000
Model:	FB-D.....

3. Features:

Pneumatic butterfly valve, is in the introduction of foreign advanced technology on the basis of special design, carefully manufactured products.

Butterfly valve with travel limit switch, solenoid valve, triplet and 0.4-0.7MPa air source can realize switching operation, and send two pairs of passive contact signals to indicate the switch of the valve.

Using intelligent control and positioning, with domestic electrical valve positioner, input 4-20mADC signal and 0.4-0.7MPa air source can achieve intelligent control, to achieve the adjustment of pressure, flow, temperature, liquid level and other parameters.

Powered by compressed air, and the valve stem drives the spool to rotate 90 ° C in the valve body, which can realize the fully open - fully closed action.

Product is divided into metal seal and soft seal according to its sealing performance.

Advantages of compact structure, small size, reliable operation, good sealing, easy maintenance, convenient installation and strong adaptability.





Fabia Valve Industry (Suzhou) Co., Ltd.



+8618913247051/+8618912658215/+8618260178084



sales@fabia-china.com



fballvalve.com

Room 1305, Building 3, Jundi Business Plaza, No.3, Weihua Road, Suzhou Industrial Park